



NOTICE OF RACE
Appendix B Safety Consultation Checklist
2024 VICTORIA TO MAUI INTERNATIONAL YACHT RACE





Vic-Maui acknowledges the generous support of our

Co-hosts

Royal Vancouver Yacht Club

Lahaina Yacht Club



GOLD SPONSORS



SILVER SPONSORS



SUPPORTING SPONSORS

MOUNT GAY RUM | NORTHAM BEVERAGES LIMITED



2024 Vic-Maui International Yacht Race

NOTICE OF RACE: APPENDIX B

Safety Consultation Checklist

NOTE: This Checklist is condensed from the Offshore Special Regulations 2022-23 for a Category 1 Monohull race and is provided as a courtesy. In the event of a conflict between this Checklist and the Offshore Special Regulations, the full text of the Offshore Special Regulations shall apply, subject to modifications made in the Notice of Race and its Appendix A.

PERSON IN CHARGE: Boats must complete their safety consultation prior to June 5, 2024. Appointments must be set up no later than April 30, 2024. Prior to the consultation, please ensure your boat is in a suitable state of readiness with gear laid out for viewing. All boats must submit a completed and signed Checklist no later than June 19, 2024. Written confirmation that all deficiencies noted on the Checklist have been corrected must be provided to the Race Committee prior to the boat's warning signal.

INSPECTORS - Mark each inspected item with a checkmark or X or N/A. Note any deficiencies and give a copy to the *Person in Charge*. Please return a copy of the Checklist or a summary of deficiencies to the *Race Committee* as soon as possible.

Yacht _____ Sail Number _____

Make/Model _____ Year Built _____

No of crew _____ Names of Persons Attending Consultation _____

Disclaimer of Liability The safety consultation is carried out as a courtesy. An inspector cannot limit or reduce the complete and unlimited responsibility of the owner and the person in charge.

I hereby declare that I am the Person in Charge and that I have read and understand the Offshore Special Regulations and Appendix A to the Notice of Race and that my boat conforms to the requirements. In particular I understand my responsibilities listed in Sections 1.02.1 and 1.02.2.

Signature _____

Date _____

OSR Section	Requirement	Check	Comment
-------------	-------------	-------	---------

TO BE ELECTRONICALLY FILED WITH RACE COMMITTEE

Green Highlight means a new requirement in OSR or NoR
NOTE: Appendix A for 2022 and 2024

3.02.3	Proof of structural inspection of keel, rudder and steering systems by qualified person		
3.04	Proof that boat meets ISO 12217-2A, ORC Stability of 115, or equivalent		
4.15.2	Alternate steering method – Proof of deployment and use provided		
4.19.4	Proof of EPIRB registration with rescue authority		
4.20.5b	Servicing certificate to SOLAS B, ISO 9650-2 or ORC for each liferaft		
5.01.4	Certificate that each lifejacket has been inspected by person in charge in last 12 months		
6.01	World Sailing approved survival training certificate for 2/3's of the crew		
6.04	MOB practice certificate signed by all crew		
6.05.2	Recognized First Aid certificate for min. 2 of the crew		
LAID OUT ON BUNK			
3.29.1	Emergency antenna for each type of installed radio transceiver		
3.29.5	Watertight handheld VHF radio transceiver stowed in grab bag		
3.29.6	Independent receiver capable of receiving weather, could be a satellite device		
4.08	First aid kit and approved first aid manual		
4.09	Foghorn		
4.11	Charts (including paper), light list, plotting equipment		
4.16	Tools, spare parts, method to disconnect/sever standing rigging		
4.22.1 b	AIS crew personal overboard beacon unit for each crew member		
4.23	SOLAS Flares, 4 red hand-held, 2 orange smoke - <u>all in date</u>		
5.01.1 a	Approved lifejackets for each crew c/w whistle, lifting loop, crotch or thigh straps & integral harness		
5.01.1 b,c,d	Each lifejacket has position light, marked with name & spray hood		
5.01.2/ NOR	Spare gas inflation cylinder and activation head for each lifejacket. For identical spares 1 per 2 lifejackets okay.		
5.01.3	Spare lifejacket		
5.02.1	ISO 12401 Safety harness for each crew - <u>integrated with lifejacket</u>		
5.02.2, 3	For each crew, max 2 m tether to ISO12401, with overload flag and mid tether hook or extra 1m. tether		
BELOW DECK INSPECTION			
3.06.1	At least 2 exits, at least 1 forward of the foremost mast		

3.08.3	Inward opening hatches labelled "NOT TO BE OPENED AT SEA"		
3.10	Sea cocks or valves on through-hull openings below waterline		
3.12	Heel of keel-stepped mast is secured to structure		
3.18	Toilet, permanently installed		
3.19.2	Bunks, permanently installed		
3.20	Cooking stove, securely fastened with fuel shut-off		
3.21.1	Water delivery pump and tanks divided into at least 2 compartments		
3.21.2	Tanks or watermaker to provide 3 L per person per day		
3.21.3	Min. of 9 L emergency water in sealed containers		
3.22	Adequate hand holds below deck		
3.27.4	Spare bulbs or appropriate spares for navigation lights		
3.28.4 a	Separate starting battery or hand-starting device		
3.28.4 b	All batteries are of sealed type (flooded allowed if installed before 2012)		
3.29.2	25W DSC enabled VHF w/ masthead antenna & programmed MMSI		
3.29.3	One hand-held satellite telephone, configured at all times to receive calls		
3.29.13	An AIS Transponder w/ shared masthead antenna or dedicated antenna 15" in length and 10' above waterline		
3.29.14	125W DSC MF/HF marine SSB transceiver w/ antenna and ground OR 2 approved satellite comm devices.		
NOR	Test of SSB or Satphone email capability with Race Committee prior to arrival in Victoria (test to be conducted in accordance with Communications Plan)		
4.03	Tapered soft wood plug at each through-hull opening		
4.05.1	A fire blanket adjacent to every cooking device		
4.05.2	Min. 2 fire extinguishers, 2 kg each, accessible, in different parts of the boat		
4.12	Safety equipment location chart		
4.19.1	406 MHz EPIRB with GPS and battery expiry after August 2020		
4.21	A grab bag for each liferaft		
4.30.1	Fixed or portable 200 l/m emergency pump with hose and power connections		
AT HELM READY FOR DEPLOYMENT			
4.22.2 c	GPS recording crew overboard location, activated within 10sec		
4.22.3	Lifebuoy with self-igniting light and drogue close to helm		
4.22.4, 5	2nd lifebuoy, with light, drogue, whistle & float with flag 2m (6') above water. One lifebuoy shall depend on permanent buoyancy		
4.22.6	Inflatable lifebuoy and automatic devices serviced		

4.22.7	Heaving line, preferably 'Throwing sock' type, 15-25 m (50-75')		
4.22.8	A recovery sling with 120' of line (Lifesling or equivalent)		
ON DECK, STOWED OR READY FOR DEPLOYMENT			
4.02	A 1 m2 (11 ft2) solid hi-viz area for display on coachroof		
4.06	2 suitably sized anchors and rode, one suitable for anchoring in 50' with coral		
4.07 a	Watertight high powered searchlight with spare batteries and bulbs		
4.07 b	Watertight flashlight with spare batteries and bulbs		
4.20.1 a	<u>SOLAS, ISO 9650-2, ORC Liferaft(s)</u> capable of carrying the whole crew		
4.20.2	SOLAS B or ISO 2 Liferaft pack		
4.20.3	Liferaft(s) stowed in rigid container on deck or in dedicated locker, or in valise in dedicated locker. Boats older than 2001 can store <40 Kg (88 lb) valise below deck. Painter secured to boat and Able to get to lifelines in 15 s.		
4.25	A strong, sharp knife on deck or cockpit, sheathed and securely restrained		
RIGGED/FITTED TO DEMONSTRATE USE			
3.27	Navigation lights of specified intensity, not obscured when sailing		
3.27.3	Reserve navigation lights, powered independently		
4.01.2	Alternate method for displaying sail letters		
4.04.1,2	2040 Kg jacklines to permit movement between work areas and cockpit with min. of unclipping - in place during safety consultation		
4.04.3 a,c	Clipping points at work stations so that 2/3 of crew can clip on without jacklines		
4.04.3 b	Clipping points so that crew are able to clip on before coming on deck and unclip after going below		
4.10.1	Radar reflector, 30 cm (12") dia octahedral or minimum RCS of 2 m ²		
4.15.1	Emergency tiller		
4.26.1	Storm trysail or mainsail reefing to reduce main luff by 50% (if furling mainsail, must have trysail)		
4.27.1 c	Sheeting positions for trysail and storm jib - sails must be set during safety consultation or picture provided		
4.26.2	Heavy weather jib		
4.26.3	Storm jib with dayglo		
4.27.4	Means to attach heavy/storm headsail independent of luff groove		
BOAT CONSTRUCTION AND FITTING OUT			
2.04.1	All equipment is readily available, adequately sized and functions and is in-date		

2.04.2	Heavy items such as batteries, floorboards, anchors, propane bottles, engine are permanently installed or securely fastened		
3.01.4	Strongly recommended that mast and in-mast furling be inspected		
3.02.1	The boat is watertight and all openings capable of being immediately secured		
3.08.1	Forward hatches open outward only, except on coachroof <110 in2		
3.08.2	Hatches are attached, above water at 90° heel & capable of being shut if capsized		
3.08.4	Companionway drop panels attached and can be secured in place. Operable from interior and exterior		
3.08.5 3.08.6	Companionway sill is above local sheerline, or acceptable blocking panel alternative		
3.09	Cockpit is above waterline, strong, and all openings can be closed and secured. Drains are unobstructed openings 4 x 3/4" or equivalent		
3.14.1	Lifelines taut and, in combination with pulpits, surround entire <u>working</u> deck		
3.14.6	Lifelines are uncoated stainless steel: 4mm for under 43 ft, 5 mm for over		
3.17	Minimum 25 mm (1") toerail around foredeck		
3.23.1 a	2 strong buckets, each with lanyard and 9 l (2.4 US Gal) min capacity		
3.23.1 b	2 permanent manual bilge pumps, 1 operable from below deck with hatches closed		
3.23.3	Bilge pumps not discharged into closed cockpit or cockpit drains		
3.23.4	Bilge pumps readily accessible for maintenance and cleaning		
3.23.5	Removable bilge pump handles have lanyard		
3.24 a	Magnetic compass, independent of power supply, with deviation chart		
3.24 b	2nd magnetic compass, unpowered, may be hand-held		
3.25	No less than 2 halyards per mast, each capable of hoisting a sail, and not secured to mast in a way that requires a person to go aloft		
3.28.1	Suitable inboard propulsion engine protected from heavy weather with permanent fuel, cooling and power supply		
3.28.1	Propulsion engine provides minimum speed of SQRT (LWL) in ft		
3.28.3	Sufficient fuel to charge batteries and motor at above speed for 8 hours		
4.01.1	Sail letters/numbers		
4.13.1	Knotmeter or log		
4.13.2	Depth sounder		
4.17	Boat's name on buoyant equipment		
4.18	Marine grade retro-reflective material on buoyant equipment		